



StimMax™

non-conventional • bio-derived • nano-scale

Stimulation CR-1000

Stimulation Fluids for Maximum Flow

DESCRIPTION

Readily biodegradable and made with domestically sourced renewable resources, StimMax™ CR-1000 is a one-step (no mixing) two part non-conventional mixture of bio-derived solvents and surface acting agents specifically formulated to "unblock" the flow of oil or gas due to water build up in the well and disperse it while increasing production 50-100% and, even more in some documented cases. Each year, thousands of wells experience significant production reductions or are abandoned altogether due to "wet gas" condensing as temperatures approach the dew point causing water to block the flow. StimMax is safe for the environment as well as oil field operators and is a clean way to address this issue without the use of superheated steam or dangerous acids that may contaminate oils or gas. Unlike toluene and other benzenes, it is not a solvent and will never mix with or degrade the oil and gas, which will not be compromised and is fully compatible with production facilities and refining processes after treatment.

APPLICATION

StimMax CR-1000 is a one-step application best used during routine maintenance of low producing wells. When production is halted for service work, a treatment ensures that bore restriction ceases to be an issue. Mix StimMax CR-1000 on site with water and apply to well per instructions.

DIRECTIONS For USE

The amount of product necessary will vary depending on the depths of the well, the size of the bore, specific down-hole conditions and the type of crude; not to mention the substantiation of specific formation restrictions. Once a diagnosis is made, then proceed by diluting the product on-site with water (fresh or salt) and inject into the well bore under pressure. Cap the well and allow StimMax to dwell in the bore for 24 hours under pressure. Upon completion of treatment, the oils and contaminants will be pumped out with the initial flow and can then be easily separated for disposal.

PHYSICAL PROPERTIES	
Appearance:	Light Amber Liquid
Viscosity:	Slight
Odor:	Faint Soapy Odor
Physical State:	Liquid
Solubility in Water:	Complete
pH:	6.0
Specific Gravity @ 25° C:	0.985
Vapor Density:	5 lbs. /Gallon
Stability:	Stable
Availability:	330 Gallon Tote



Go with the FLOW!