



StimMax™

non-conventional • bio-derived • nano-scale

Stimulation PA-1000

Stimulation Fluids for Maximum Flow

DESCRIPTION

Readily biodegradable and made with domestically sourced renewable resources, StimMax™ PA-1000 is a one-step (no mixing) two part non-conventional mixture of bio-derived solvents and surface acting agents specifically formulated to dissolve, disperse and dispense petroleum based obstructions at the nano-scale to promote a “healthy formation” which leads to increase pressure which in turn leads to increased production...50-100% increase with, even more in some documented cases. Each year, thousands of wells experience significant production reductions or are abandoned altogether due to excess buildup of paraffin, asphaltenes and other petroleum based obstructions in the perforations of the well. StimMax is safe for the environment as well as the oil field operators and is a clean way to address this issue without the use of superheated steam or dangerous acids that may contaminate oils or gas. Unlike toluene and other benzenes, it is not corrosive or caustic and will never mix with or degrade the oil and gas, which will not be compromised, and is fully compatible with production facilities and refining processes after treatment.

APPLICATION

timMax PA-1000 is a one-step application best used during routine maintenance of low producing wells. When production is halted for service work, a treatment of StimMax ensures that bore restriction ceases to be an issue.

DIRECTIONS For USE

The amount of product necessary will vary depending on the depths of the well, the size of the bore, specific down-hole conditions and the type of crude; not to mention the substantiation of specific formation restrictions. Once a diagnosis is made, proceed by injecting StimMax into the well bore according to instructions. Cap the well, inject either fresh or brine water and allow StimMax to dwell in the bore for 24-48 hours under pressure. Upon completion of treatment, the oils and contaminants will be pumped out with the initial flow and can then be easily separated for disposal.

PHYSICAL PROPERTIES	
Appearance:	Light Amber Liquid
Viscosity:	Slight
Odor:	Faint Soapy Odor
Physical State:	Liquid
Solubility in Water:	Complete
pH:	6.5
Specific Gravity @ 25° C:	0.985
Vapor Density:	4 lbs. /Gallon
Stability:	Stable
Availability:	330 Gallon Tote

